

### Standard Size

| Model     | Dimension<br>H x W x D(mm)<br>(Gasket Excluded) | Airflow (CMM) |         |
|-----------|---|---------------|---------|
|           |   | 0.5m/s        | 0.85m/s |
| LL3407-61 | 305 x 305 x 52                                  | 2.3           | 3.9     |
| LL3401-61 | 610 x 305 x 52                                  | 4.8           | 8.2     |
| LL3401-62 | 610 x 610 x 52                                  | 10.1          | 17.2    |
| LL3401-67 | 610 x 760 x 52                                  | 12.7          | 21.7    |
| LL3401-63 | 610 x 915 x 52                                  | 15.4          | 26.3    |
| LL3401-64 | 610 x 1220 x 52                                 | 20.8          | 35.3    |

\* Airflow(CMM) = (H-0.028)m x (W-0.028)m x Face Velocity m/s x 60sec

\* For any other size or design please contact us.

### Specification

| Face Velocity<br>(m/s) | Initial Pressure Drop<br>(Pa) | Efficiency<br>(0.3µm) |
|------------------------|-------------------------------|-----------------------|
| 0.5                    | 110                           | ≥99.99%               |
| 0.85                   | 200                           | ≥99.99%               |

Lamination : ±20%

Scanning Test : Silica

Conformed : IES-RP-CC001.3


Safety(Optional) : FM4920

### Materials, Use Conditions

|                          |  |
|--------------------------|--|
| Media                    | Low Organic Compounds ·<br>Low Boron Glass Fiber |
| Separator                | Polyester Yarn                                   |
| Frame                    | Anodized Aluminum                                |
| Face Guard               | Anodized Aluminum                                |
| Sealant                  | Urethane Resin                                   |
| Gasket                   | EPDM Sponge                                      |
| Use Max. Temperature     | ≤80°C  |
| Use Moment Max. Humidity | <100%RH, without dew                             |

### Model Configuration

LL3401 - 6 □ □ AA



\* Specifications are subject to change without notice.

#### TAIWAN NITTA FILTER CO., LTD.

Head office : Chia Hsin Building 10 Fl., Room No. 1005, 96 Chung Shan N. Rd., Sec. 2, Taipei, Taiwan, R. O. C.

TEL:+886-2-2581-6296 FAX:+886-2-2563-4900

Factory : 2-1, Industrial 2nd Rd, Pinchen Industrial Park, Taoyuan. Taiwan. R.O.C.

TEL:+886-3-469-7551 FAX:+886-3-469-0260

<http://www.nitta.com.tw>

