


e SP HEPA Filter

Panel Type

eSP5H Series



Standard Size

Model	Dimension H x W x D(mm) (Gasket Excluded)	Airflow (CMM)	
		0.5m/s	0.85m/s
eSP5H-61	610 x 305 x 68	4.8	8.2
eSP5H-62	610 x 610 x 68	10.1	17.2
eSP5H-67	610 x 760 x 68	12.7	21.7
eSP5H-63	610 x 915 x 68	15.4	26.3
eSP5H-64	610 x 1220 x 68	20.8	35.3

* Airflow(CMM) = (H-0.028)m x (W-0.028)m x Face Velocity m/s x 60sec
 * For any other size or design please contact us.

Specification

Face Velocity (m/s)	Initial Pressure Drop (Pa)	Efficiency (0.3µm)
0.5	120	≥99.99%
0.85	200	≥99.97%


Lamination : ±20%
 Scanning Test : Silica
 Conformed : IES-RP-CC001.3

Materials, Use Conditions

Media	Glass Fiber
Separator	Glass Yarn
Frame	Anodized Aluminum
Face Guard	Anodized Aluminum
Sealant	Urethane Resin
Gasket	EPDM Sponge
Use Max. Temperature	≤80 °C
Use Moment Max. Humidity	<100%RH, without dew

Model Configuration

eSP5H - 6 □ □ □ AA



* Specifications are subject to change without notice.

TAIWAN NITTA FILTER CO., LTD.

Head office : Chia Hsin Building 10 Fl., Room No. 1005, 96 Chung Shan N. Rd., Sec. 2, Taipei, Taiwan, R. O. C.
 TEL:+886-2-2581-6296 FAX:+886-2-2563-4900
 Factory : 2-1, Industrial 2nd Rd, Pinchen Industrial Park, Taoyuan. Taiwan. R.O.C.
 TEL:+886-3-469-7551 FAX:+886-3-469-0260

<http://www.nitta.com.tw>

