


SPleats™

Panel Type Low Boron ULPA Filter

LB3842 Series



Standard Size

Model	Dimension H x W x D(mm) (Gasket Excluded)	Airflow (CMM)	
		0.5m/s	0.85m/s
LB3848-61	305 x 305 x 86	2.3	3.9
LB3842-61	610 x 305 x 86	4.8	8.2
LB3842-62	610 x 610 x 86	10.1	17.2
LB3842-67	610 x 760 x 86	12.7	21.7
LB3842-63	610 x 915 x 86	15.4	26.3
LB3842-64	610 x 1220 x 86	20.8	35.3

* Airflow(CMM) = (H-0.028)m x (W-0.028)m x Face Velocity m/s x 60sec

* For any other size or design please contact us.

Specification

Face Velocity (m/s)	Initial Pressure Drop (Pa)	Efficiency (0.1~0.2μm)
0.5	110	≥99.999% (5N)
0.85	190	≥99.999% (5N)

Lamination : ±20%

Scanning Test : Silica


Conformed : IES-RP-CC001.3

Materials, Use Conditions

Media	Low Boron Glass Fiber
Separator	Polyester Yarn
Frame	Anodized Aluminum
Face Guard	Anodized Aluminum
Sealant	Urethane Resin
Gasket	EPDM Sponge
Use Max. Temperature	≤80°C
Use Moment Max. Humidity	<100%RH, without dew

Model Configuration

LB3842 - 6 □ □ □ AA



* Specifications are subject to change without notice.

TAIWAN NITTA FILTER CO., LTD.

Head office : Chia Hsin Building 10 Fl., Room No. 1005, 96 Chung Shan N. Rd., Sec. 2, Taipei, Taiwan, R. O. C.

TEL:+886-2-2581-6296 FAX:+886-2-2563-4900

Factory : 2-1, Industrial 2nd Rd, Pinchen Industrial Park, Taoyuan. Taiwan. R.O.C.

TEL:+886-3-469-7551 FAX:+886-3-469-0260

<http://www.nitta.com.tw>

